

海宁杜勒泰新材料有限公司 HAINING DULETAI NEW MATERIAL CO.,LTD DURASUNTEX

DLT-AH1000 Series

100% Solution Dyed Acrylic **Solar Fabric Collection**

>> TEFLON PTFE TREATMENT

Our material has Teflon® PTFE treatment, the acrylic fiber is soaked with a Teflon-based coating that has the remarkable property of being both hydrophobic (water shedding) and oleophobic (oil shedding). Water cannot readily wet out the surfaces. The water droplets behave like mercury when confronted with the coated surface. Teflon coatings create a water-repellant (hydrophobic) and oil-repellant (oleophobic) surface to repel water, dust, oil, and dirt on surfaces allowing for easy-clean.











About 100% Solution Dyed Acrylic Fabric

Solution dyed acrylic fabric is a perfect choice for all outdoor application because of its outstanding fade resistant performance and olorfastness to water, colorfastness to washing, and color reproducibility. Its ultraviolet blocking agents protect the fabrics from fast aging caused by the effect of UV radiation so it is well recognized to be very durable under various weather conditions.

During manufacturing the acrylic fiber is dyed while it is still in a viscous form, we blend pigment and polymerthe so color is locked in before the fiber even becomes a solid. This allows the color all the way through the yarn once it is extruded. This process allows the color to be mixed into the solution thoroughly, bringing the color all the way through the fiber once it is extruded, creating a colorfast fabric much stronger than that obtained by dyeing the thread.

Solution dyed acrylic fabric has mold resistant qualities (mildew grows on dirt, pollen and other organic matter, so simple routine cleanings will prevent mildew from forming). In addition, the solution-dyed acrylic waterproof fabric can be bleached to remove tougher stains without compromising color.

5 Years Warranty

Our fabric guarantee 5 years limited warranty. Warranty coverage include fading or losing colors due to the color performance degradation in normal environment.

Cleaning Instructions

Stains on the fabric can be cleaned with 37°C low-temperature water, with neutral soap liquid. You can use a brush to brush lightly. After washing the stains, just dry naturally, do not twist, so as to avoid fabric deformation, and do not use temperature ironing, so as to avoid high temperature discoloration.

Material Applications:

▶ Pergolas and Loggias ▶ Awnings ▶ Umbrellas ▶ Shade Sails



▶ Marine Covers



DLT-AH1000





DuraSuntex DLT-AH1000 Series			
Material:	100% Acrylic Solution Dyed	Tensile Strength:	870N Warp / 1000N Weft
Technics:	Teflon® PTFE Treatment	Water Repellency:	Level 5 [Spray test: 20±2c ISO 4920:2012E]
Width:	120cm (47") / 150cm (59")	Alcohol Test:	Level 4 [0.6cm 10s 45° AATCC 193]
Weight:	300gsm	Oil Test:	Level 3 [0.6cm 30s 45° 27.3m N/m AATCC 118]
Roll Length:	60/100meters	UV Test:	50+ [Rated UPF AATCC 183-2014]
Tearing Strength:	42N Warp / 38N Weft	Water Pressure:	>300mm [Hydrostatic ISO 811:2018]
Colour Fastness to Rubbing:		Dry staining 4-5/ Wet staining 4-5 [ISO 105-X12:2016]	
Colour Fastness to Artificial Light:		Level 8 [ISO 105 B02:2014]	
Colour Fastness to Artificial Weathering:		Level 7 [ISO 105 B04:1994]	
Colour Fastness to Light:		Level 3-4 After 2000 hours change in shad [AATCC TM 16.3-2014]	

Teflon® PTFE treatment, the acrylic fiber is soaked with a Teflon-based coating that has the remarkable property of being both hydrophobic (water shedding) and oleophobic (oil shedding). Water cannot readily wet out the surfaces. The water droplets behave like mercury when confronted with the coated surface. Teflon coatings create a water-repellant (hydrophobic) and oil-repellant (oleophobic) surface to repel water, dust, oil, and dirt on surfaces allowing for easy-clean.


Material Features
























Repeat: 25cm




DLT-AH1101




Repeat: 30cm



DLT-AH1102



Repeat: 30cm




DLT-AH1103



Repeat: 30cm



DLT-AH1104




Repeat: 30cm



Repeat: 30cm




Repeat: 30cm



Repeat: 30cm



DLT-AH1105




DLT-AH1106




DLT-AH1107



DLT-AH1108




Repeat: 30cm




DLT-AH1109




Repeat: 30cm



DLT-AH1110



Repeat: 30cm




DLT-AH1111




Repeat: 18.7cm



DLT-AH1112



Repeat: 18.7cm



DLT-AH1113



Repeat: 18.7cm



DLT-AH1114



Repeat: 18.7cm



DLT-AH1115







海宁杜勒泰新材料有限公司 HAINING DULETAI NEW MATERIAL CO.,LTD



OEM Customer Centric Service

Our sales manager has 10+year experience in this field. We have comprehensive knowledge and resources both in production and international business. All your requirements and problems will be handled professionally.

Joint R&D

Our research and development section is open to our clients. We are willing to share new technology and work with our cleints together to upgrade their products and developing new ones together.

Suprior Quality Control

We focus on durable products and long term business relationship with clients. Stable quality is the first consideration. We have fabric testing lab and quality traceability system to eusure everthing is undercontrol.







Web Site



Video Intro